

Bookstack

502 on OIDC logout

Edit `/config/nginx/site-confs/default.conf` inside the container. On the host, it's under whatever directory you mapped to `/config`, so something like `./bookstack/config/nginx/site-confs/default.conf`.

Open it and find the PHP block, which in the linuxserver image looks like this:

Add the buffer directives inside it:

```
location ~ /\.php$ {
    fastcgi_split_path_info ^(.+\.php)(/.+)$;
    fastcgi_pass 127.0.0.1:9000;
    fastcgi_index index.php;
    include /etc/nginx/fastcgi_params;

    fastcgi_buffer_size 32k;
    fastcgi_buffers 16 16k;
    fastcgi_busy_buffers_size 32k;
}
```

Then test and reload without restarting the container:

```
docker exec bookstack nginx -t && docker exec bookstack nginx -s reload
```

(Replace `bookstack` with your container name.)

The linuxserver image only creates `default.conf` on first run and won't overwrite it on updates, so your edit will persist. If a future image update introduces a new default, it saves it as `default.conf.sample` next to yours rather than replacing it.

If the error persists after this, check your `.env` (in `/config/www/.env`) for `SESSION_DRIVER`. If it's set to `cookie`, switching it to `file` or `database` is the other big lever for shrinking headers.

Revision #3

Created 2026-10-23 07:11:41 UTC by etorres

Updated 2026-10-23 07:13:30 UTC by etorres